



Opti Max1111 Model Options

Listed below are the model options for the Opti Max1111 node. For ordering information, please use our real-time Product Configurator Wizard located on the ARRIS website.

	OM11xx Series
--	---------------

G	1 GHz
---	-------

J	42/54MHz
H	65/85MHz
R	85/105MHz

C	45 to 90Vac Remote powered w/surge protection
D	110Vac US local powered
E	230Vac UK local powered
<p>Power plug designs for local power.</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>110VAC American Standard</p> </div> <div style="text-align: center;">  <p>230VAC UK Standard</p> </div> </div>	

B	Strand mount-complete
H	Optical lid-upgrade with RF module

1	Standard receiver-optical AGC user configurable
---	---

H	17.5dB
---	--------

1	FC/APC
2	SC/APC
3	FC/UPC
4	SC/UPC

A	Single Transmitter 1550 nm DFB
B	Single Transmitter 1310nm DFB
C	Single Transmitter CWDM 1471 nm DFB
D	Single Transmitter CWDM 1491 nm DFB
E	Single Transmitter CWDM 1511 nm DFB
F	Single Transmitter CWDM 1531 nm DFB
G	Single Transmitter CWDM 1551 nm DFB
H	Single Transmitter CWDM 1571 nm DFB
I	Single Transmitter CWDM 1591 nm DFB
J	Single Transmitter CWDM 1611 nm DFB

0	None
1	Factory-installed WDM

1	FC/APC
2	SC/APC
3	FC/UPC
4	SC/UPC

The Opti Max1111 model options are for “reference only” and should not be used for ordering. Contact your ARRIS sales professional for ordering information. You may also use our Product Wizard Configurator located on the ARRIS website.