



Security Alarm Cable CMR Unshielded Stranded

PVC Insulated stranded bare copper conductors, twisted, with an overall gray PVC jacket with rip cord. Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(ETL)us.

Applications

- Security Systems
- Intercom Systems
- Sound/Audio Systems
- Power-Limited Controls

Compliance

- NEC Articles:
 - 22-16 AWG: FPLR/760, CMR/800, CL3R, CL2R/725
 - 14-12 AWG: FPLR, CL3R
- ETL Verified
- RoHS Compliance

Physical Characteristics

- Conductor: Stranded Bare Copper
- Insulation:
 - 22 AWG: 0.007"
 - 18-16 AWG: 0.010"
 - 20 AWG: 0.008"
 - 14-12 AWG: 0.012"
- Jacket: PVC
- Shielding: Aluminum Mylar
- Voltage Rating: 300 V
- Temperature Rating: 75°C

Color Code Chart

Conductor	Color	Conductor	Color
1	Black	7	Orange
2	Red	8	Yellow
3	White	9	Purple
4	Green	10	Gray
5	Brown	11	Pink
6	Blue	12	Tan

*14-12 AWG are not recognized by c(ETL).



Put-Ups

- Cable is supplied on a 1,000ft. wooden spool or in a pull box

Part #	AWG/ Conductors	Strands	Jacket Thickness	Nominal O.D.
ASC-1898/122	12/2	19	.015" (.38mm)	.268" (6.81mm)
ASC-1896/142	14/2	19	.015" (.38mm)	.234" (5.94mm)
ASC-1897/144	14/4	19	.015" (.38mm)	.276" (7.01mm)
ASC-1893/162	16/2	19	.015" (.38mm)	.184" (4.67mm)
ASC-1894/163	16/3	19	.015" (.38mm)	.196" (4.98mm)
ASC-1895/164	16/4	19	.015" (.38mm)	.216" (5.49mm)
ASC-1881/182	18/2	7	.015" (.38mm)	.161" (4.09mm)
ASC-1888/183	18/3	7	.015" (.38mm)	.171" (4.34mm)
ASC-2928/184	18/4	7	.015" (.38mm)	.188" (4.78mm)
ASC-1889/186	18/6	7	.015" (.38mm)	.226" (5.74mm)
ASC-1890/188	18/8	7	.015" (.38mm)	.248" (6.30mm)
ASC-4429/1810	18/10	7	.015" (.38mm)	.294" (7.47mm)
ASC-4108/202	20/2	7	.015" (.38mm)	.142" (3.61mm)
ASC-4109/203	20/3	7	.015" (.38mm)	N/A
ASC-4110/204	20/4	7	.015" (.38mm)	.165" (4.19mm)
ASC-4172/222	22/2	7	.015" (.38mm)	.128" (3.25mm)
ASC-3521/223	22/3	7	.015" (.38mm)	.135" (3.43mm)
NPNB-12204R	22/4	7	.015" (.38mm)	.148" (3.76mm)
ASC-1931/226	22/6	7	.015" (.38mm)	.177" (4.50mm)
ASC-1891/228	22/8	7	.015" (.38mm)	.192" (4.88mm)
ASC-1892/2210	22/10	7	.015" (.38mm)	.226" (5.74mm)
ASC-4470/2212	22/12	7	.015" (.38mm)	.233" (5.92mm)

©2015 CRN Solutions Inc. dba. Primus Cable
All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan. 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

PrimusCable.com - (951) 824-1571

