

# DLPS-15DF SPECIFICATIONS

## ELECTRICAL SPECIFICATIONS:

FREQUENCY: 5-1000 MHz

INSERTION LOSS: GUARANTEED

5-40 MHz >-40.0 dB

54-60 MHz <1.5 dB

60-75 MHz <1.0 dB

75-1000 MHz <0.5 dB

RETURN LOSS: GUARANTEED

54-60 MHz >16 dB

60-75 MHz >18 dB

75-1000 MHz >18 dB

EMI SHIELDING: >130 dB (5-1000 MHz)

SWITCHING VOLTAGE: 135V Peak Min. 165V Max.

RESPONSE TIME: Less than 1 nanosecond

CURRENT SUPPRESSION: 500 Amps. (2 X 10 microsecond pulse)

## MECHANICAL SPECIFICATIONS:

DIMENSIONS: 2.35 in. W x 1.48 in. H x .64 in D

59.7 mm W x 37.6 mm H x 16.26 mm D

OPERATING TEMPERATURE:

(Ambient) -40 to +140 Degrees Fahrenheit

-40 to +60 Degrees Celsius (Centigrade)

THIS DOCUMENT IS THE PROPERTY OF CABLE INNOVATIONS. SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## CABLE INNOVATIONS

130 STANLEY COURT

LAWRENCEVILLE, GA 30045

PRODUCT SPECIFICATION, DLPS-15DF

DWG # 6215DF00

SHEET 1

REV A