
Drop Connectors

UltraEase® BNC, RCA & Pin Type "F" Compression Product Information



Broadband Products

Connector Specifications

BNC:

75 Ohm BNC interface with gold plated push-out pin

RCA:

Gold plated pin and outer conductor for compatibility with consumer equipment

Pin Type "F":Male interface meets SCTE-IPS-SP-401 after

installation

The Corning Gilbert UltraEase® family includes RCA, BNC and pin-type "F"male connectors. The RCA and BNC connectors are available for 59, 6, and mini coax series of cables. The pin-type "F" male connector is available for mini coax cables.

All of these connectors have an innovative pushout pin (7,153,159) that eliminates blind entry when installing. In addition, the UltraEase compression technology provides 360 degrees of contact to the cable, providing excellent RF shielding integrity.

The UltraEase design gives the lowest activation force available in a high performance compression connector. This one-piece design eliminates any loose parts. Connectorization can be performed rapidly and consistently without the risk of misalignment of multiple parts.

For information on "F" feedthru UltraEase for 59 and 6 series cables, see product infomation G-1400-642.



RCA

065



Materials and Construction of Connector Components

Body:

Black UV Resistant Polymer

Shell & Body:


C36000 Brass Alloy with Nickel Plating

Post:

C36000 Brass Alloy with Bright Acid Tin Plating

Cable Preparation


One step cable preparation of 1/4 "[6.5 mm] Braid and Dielectric and 1/4": [8.0 mm] center conductor



Product Features and Benefits

- 360° radial compression (patent pending) at the connector/cable interface provides excellent RF shielding
- Each connector is marked by a color coded label, displaying "GILBERT" and the cable series
- All series of connectors incorporate a gold plated push-out pin to eliminate blind entry. (7,153,159)
- One-piece construction eliminates lost or mismatched components; all center pins are incorporated into the connector body

- · One-step cable preparation using industry-accepted trim tools
- Uses commonly available compression tools; "F" series connectors are compatible with existing UltraSeal® compression tools
- · All exposed metal surfaces are nickel plated on BNC and "F" series connec tors for superior corrosion resistance
- "F" series is compatible with industry accepted security sleeves
- · RCA connector series have gold plated interfaces.



Ordering Information

| Part Number | Color Code | Cable Type | Braid Coverage | Pkg. Qty | Prep. Tool | Compression Tool |
|---------------|------------|-------------|-----------------------|------------|-------------|--------------------|
| GAF-UE-M | Red | Series Mini | 60% to Tri-shield | 100 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA** |
| GAF-UE-MQ | Orange | Series Mini | Quad | 100 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA** |
| GA-RCA-UE-59 | Black | Series 59 | 60% to Tri-shield | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-RCA-UE-59Q | Green | Series 59 | Quad | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-RCA-UE-6 | Gold | Series 6 | 60% to Tri-shield | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-RCA-UE-6Q | Silver | Series 6 | Quad | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-RCA-UE-M | Red | Series Mini | 60% to Tri-shield | 50 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA |
| GA-RCA-UE-MQ | Orange | Series Mini | Quad | 50 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA |
| GA-BNC-UE-59 | Black | Series 59 | 60% to Tri-shield | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-BNC-UE-59Q | Green | Series 59 | Quad | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-BNC-UE-6 | Gold | Series 6 | 60% to Tri-shield | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-BNC-UE-6Q | Silver | Series 6 | Quad | 50 pieces | G-CPT-6590* | G-CAT-MULTIMEDIA |
| GA-BNC-UE-M | Red | Series Mini | 60% to Tri-shield | 50 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA |
| GA-BNC-UE-MQ | Orange | Series Mini | Quad | 50 pieces | G-LDT-MINI | G-CAT-MULTIMEDIA |

Corning Gilbert Inc. **Broadband Products** 5310 W. Camelback Rd. Glendale, AZ 85301 U.S.A.

800 528 5567 (U.S. and Canada) phone: (1) 623 245 1050 (International)

fax: 800 344 6358

(1) 623 931 0684

www.corning.com/corninggilbert info-gilbert@corning.com e-mail:

- May use G-SDT-596-250 or equivalent as an alternate
- ** May use G-CAT-UNIVERSAL-FX or equivalent as an alternate compression tool.

For information on "F" feedthru UltraEase for 59 and 6 series cables, see product infomation G-1400-642.