

Trunk & Distribution Connectors

GRS™ 3-Piece Series Product Information

Corning
Gilbert

GRS Connector Specifications

Designed to meet SCTE interface specifications

Bandwidth: 5 MHz to 1 GHz

Operating Range: -40°F to +140°F


Nominal Impedance: 75 ohms

Shielding Effectiveness: > 130 dB

Return Loss: 30 dB minimum

Insertion Loss: < 0.15 dB (pin types)

Cable Retention: Exceeds cable manufacturers' maximum pulling tension specifications



The industry leading GRS 3-piece trunk & distribution connector series is designed for optimal performance in high bandwidth, two-way and digital communication systems.

The GRS Series provides independent seizing of the cable's center and outer conductors during the installation process, guaranteeing proper cable retention. Uniquely, the GRS design compensates for potential tolerance mismatches between the cable and connector.

The connector configuration allows a full view of the center conductor entering the center conductor seizing mechanism, eliminating the "blind entry" associated with 2-piece connector installation.

Cable "pullback" is minimized, preventing cable deformation. GRS extension connectors, used extensively in system upgrades, incorporate a one-piece continuous pin, providing excellent long-term performance.


Materials and Construction of Connector Components:

ASTM 6000 aluminum alloy with gold chromate conversion coating for excellent corrosion resistance and a dry film lubricant to prevent thread galling.

Contact pins and support sleeves are brass with bright acid tin plating providing excellent RF conductivity.

O-rings are ultraviolet and ozone resistant EPDM for maximum durability.

Ordering Information¹



Type

CH*	Pin Connector (2.31" pins)
EXT*	3" Extension Connector (2.31" pins)
EXT-6*	6" Extension Connector (2.31" pins)
SP	Splice Connector
BAFF	"F" Female Connector
AFM	"F" Male Connector
TR	Cable Terminator

*Note:

All "CH" and "EXT" type connectors require a "-T" at the end of the part number when ordering.

Example:

GRS-500-CH-DU-03-T is a "Pin Connector" for .500 P3/T10 cable

Part Number Commscope P3 Times Fiber T-10

GRS-412- TYPE -DU-01	.412
GRS-500- TYPE -DU-03	.500
GRS-625- TYPE -DU-02	.625
GRS-750- TYPE -DU-01	.750
GRS-875- TYPE -DU-02	.875
GRS-1000- TYPE -DU-01	1.000

Commscope QR

GRS-320- TYPE -QR	.320 (7C)
GRS-540- TYPE -QRP	.540
GRS-715- TYPE -QRP	.715
GRS-860- TYPE -QRP	.860
GRS-1125- TYPE -QR	1.125

Times Fiber TX

GRS-480- TYPE -TX	.480
GRS-565- TYPE -TX	.565
GRS-700- TYPE -TX	.700
GRS-840- TYPE -TX	.840
GRS-1160- TYPE -TX	1.160

Trilogy MC²

GRS-440- TYPE -MC2	.400
GRS-500- TYPE -MC2	.500
GRS-650- TYPE -MC2	.650
GRS-750- TYPE -MC2	.750
GRS-1000- TYPE -MC2	1.000

Corning Gilbert Inc.
Broadband Products

5310 W. Camelback Rd.
Glendale, AZ 85301 U.S.A.

phone: 800 528 5567 (U.S. and Canada)
(01) 623 245 1050 (International)

fax: 800 344 6358
(01) 623 931 0684

website: www.corning.com/corninggilbert
e-mail: info-gilbert@corning.com